

Door Selector Page – Wood

Bullet resistant wood doors are manufactured from solid wood cores lined with UL1, 2, or 3 bullet resistant fiberglass. Each door is customized to meet your specific requirements. Wood doors are available with a variety of glazing arrangements. Existing frames can be used, or a selection of ballistic anodized aluminum, steel (welded), or steel (knock-down) are available. TS-A, TS-B, and TS-G style doors have a rear retaining flange, available in painted steel or stainless steel. View windows have clamp-on style retaining flanges, available in painted steel or stainless steel.



Solid Door (SD)



Peep Hole (PH)

View Window (VW)
Standard Sizes
10x10, 12x18, 20x30

Transaction Station
Baffle Style (TS-B)
Std. Size 20"x37" at
Handicap Height

Transaction Station
Arched Style (TS-A)
Std. Size 20"x38" at
Handicap Height

Transaction Station
Glass (TS-G)
Std. Size 14"x28" at
Handicap Height

Specification:

Material: High density particle board lined with bullet resistant fiberglass (UL1, 2, or 3)

Glazing: UL1, 2, or 3 acrylics with or without an abrasion resistant coating (all styles), or UL1, 2, or 3 glass clad polycarbonate (TS-G or VW styles only).

Finish: All wood doors are available with a choice of plastic laminate, stained veneer, or painted phenolic finished.